

| | | |
|-----------------------------------|------------------------|---|
| 0037100 | DATA SHEET |  |
| valid from: 20.01.2025 | UNITRONIC® LiHH | |

Application

UNITRONIC® LiHH is a halogen free cable for low frequency applications. The cable is designed for fixed installation and for conditional flexible use. It is used in dry and damp interiors but not appropriate for outside usage.
The cable is used for data processing, measurement and control engineering, safety related systems and as electronic cables.

Design

| | |
|--------------------------|--|
| Design | Design based on standard VDE 0812 and EN 50288-7 |
| Certification | EN 13501-6 and EN 50575 Classification of fire behaviour (article/dimension range see www.lappkabel.com/cpr) |
| Conductor | fine wire strands of bare copper acc. to IEC 60228 resp. EN IEC 60228, class 5 |
| Insulation | special Polyolefin-based compound |
| Core identification code | acc. to DIN 47100 |
| Cable assembly | cores are stranded in layers, optionally with fillers |
| Outer sheath | special halogen-free compound colour: pebble grey (similar RAL 7032) |

Electrical properties at 20 °C

| | |
|-----------------------------|---|
| Conductor resistance | 0.14 mm ² : max. 138.0 Ω/km 0.25 mm ² : max. 79.0 Ω/km 0.34 mm ² : max. 57.0 Ω/km 0.5 mm ² : class 5 0.75 mm ² : class 5 1 mm ² : class 5 1.5 mm ² : class 5 |
| Specific volume resistivity | > 20 G Ω x cm |
| Mutual capacitance | C/C: approx. 80 nF/km (at 800 Hz) |
| Inductance | approx. 0.65 mH/km |
| Maximum operating voltage | 250 V (not intended to be used in conjunction with low impedance sources, such as power grids) |
| Test voltage | 1200 V |

Mechanical and thermal properties

| | |
|------------------------|---|
| Minimum bending radius | occasional flexing: 10 x outer diameter fixed installation: 4 x outer diameter |
| Temperature range | occasional flexing: -5 °C up to +70 °C fixed installation: -40 °C up to +80 °C |
| Flammability | flame retardant acc. to IEC 60332-1-2 resp. EN 60332-1-2 |
| Halogen free | acc. to IEC 60754-1 resp. EN 60754-1 |
| Corrosivity of gases | acc. to IEC 60754-2 resp. EN 60754-2 |
| Smoke density | acc. to IEC 61034-2 resp. EN 60034-2 |
| Toxicity | acc. to EN 50305 |

General requirements

These cables are conform to EU-Directive 2014/35/EU (Low Voltage Directive) and to EU-Directive 2011/65/EU (RoHS, Restriction of the use of certain hazardous substances).
A part of these cables (see www.lappkabel.com/cpr) are classified acc. to the EU-Regulation no. 305/2011 (CPR).

Environmental information

These cables meet the substance-specific requirements of the EU Directive 2011/65/EU (RoHS).

| | | |
|--------------------|-----------------------|-------------|
| Creator: PESA/PDC | Document: DB0037100EN | Page 1 of 1 |
| Released: ALTE/PDC | Version: 08 | |