

22260002	DATA SHEET	
Valid from: 17.09.2018	AB-B4-M12L-8-C	

Description

- Sensor/actuator box
- Connection methods: quick locking and LED pluggable master cable connection and double-occupied slots
- slots: 4



Number of slots:	4
Nominal voltage U : _N	24 V DC
Max. current carrying capacity per path:	2 A
Total current:	1x10 A
Total rated current (for electrical isolation):	2x8 A
Connection type:	pluggable master cable connection
Current carrying capacity per slot:	4 A
Number of poles:	5
Degree of protection:	IP65/IP67/IP69K
Status display:	LEDs
Inflammability class acc. to UL 94:	V0
Contact surface material:	Gold-plated
Material, O-ring:	NBR
Material of the moulding mass:	PUR
Material of threaded sleeve:	Zinc die-cast
Material of threaded sleeve surface:	Nickel-plated
Tightening torque slot sensor/actuator cable:	0.4 Nm
Tightening torque screw plug:	0.4 Nm


Conductor data

Slot/position = Wire colour or connection:	1 / 4 (A) = 1 / 4
--	-------------------


Creator: FELI1/PDP Released: IVSE1/PDP	Document: DB22260002EN Version: 04	Page 1 of 3
---	---------------------------------------	-------------

22260002	DATA SHEET	
Valid from: 17.09.2018	AB-B4-M12L-8-C	


Technical drawing



Circuit diagram





Example:




Creator: FELI1/PDP Released: IVSE1/PDP	Document: DB22260002EN Version: 04	Page 2 of 3
---	---------------------------------------	-------------

22260002	DATA SHEET	
Valid from: 17.09.2018	AB-B4-M12L-8-C	

Schema drawings



Potential U_{N1} and U_{N2} joint.
Potential order:
 $U_{N1} = U_{N2} = \text{slots } 1,2,3,4$



Potential separated. Potential order:
 $U_{N1} = \text{slots } 1, 3 \text{ and}$
 $U_{N2} = \text{slots } 2, 4$

Pin assignment

Slot/ position = Wire colour or connection

1 / 4 (A) = WH
 1 / 2 (B) = GY/PK
 2 / 4 (A) = GN
 2 / 2 (B) = RD/BU
 3 / 4 (A) = YE
 3 / 2 (B) = WH/GN
 4 / 4 (A) = GY
 4 / 2 (B) = BN/GN
 1-4 / 1 (+ 24 V) = BN
 1-4 / 3 (0 V) = BU
 1-4 / 5 (PE) = GN/YE

Application range

Automation, industrial machinery and plant engineering

Note

Photographs are not true to scale and do not represent detailed images of the respective products.

Creator: FELI1/PDP Released: IVSE1/PDP	Document: DB22260002EN Version: 04	Page 3 of 3
---	---------------------------------------	-------------