

19007000	DATA SHEET	
Valid from: 10.06.2026	EPIC® H-B 6 SDR	

Description

- The smallest housing out of the H-B series.
- For inserts with high properties.



General Characteristics

Series	H-B 6
Version	Socket housing
Protection cover	Yes
Locking	Single lever
Cable entry	Side, see table
Protection (DIN EN 60529)	IP 65 (latched)
Temperature Range	-40°C to +125°C

Materials and Surfaces

Housing	Aluminium alloy, powder-coated, grey
Cover	Aluminium alloy, powder-coated, grey
Lever	Steel, galvanized
Profile Seal	NBR

Approvals

UL-Approval, E-File-Number	In preparation
----------------------------	----------------

Standard

Safety Standard	IEC 61984
-----------------	-----------


Versions

Article number	Article description	Cable entry (right)	Cable entry (left)
19007000	EPIC H-B 6 SDR M20	M20	-
79015600	EPIC H-B 6 SDR M25	M25	-
19009000	EPIC H-B 6 SDRL M20	M20	M20
79016600	EPIC H-B 6 SDRL M25	M25	M25

Creator: THB01/PDP Released: TODV1/PDP	Document: DB19007000EN Version: 03	Page 1 of 2
---	---------------------------------------	-------------

19007000	DATA SHEET	
Valid from: 10.06.2026	EPIC® H-B 6 SDR	

Technical Drawings



Automation



Industrial machinery and plant engineering



Mechanical resistance



Robust



Waterproof

Info

Universal, robust metal housings size H-B 6

Application range

Plant engineering, Control engineering, Plastics industry

Remark

Photographs are not to scale and do not represent detailed images of the respective products.

Creator: THB01/PDP Released: TODV1/PDP	Document: DB19007000EN Version: 03	Page 2 of 2
---	---------------------------------------	-------------